

## Economy Occupational Noise Combination Kit



### Features

- One or more doseBadge Pro noise dosimeters
- Hand held CR308 sound level meter
- Protective Peli Case
- Everything for a noise survey
- All calibrated equipment

### Applications

- Smaller businesses with mobile workers
- Quick noise checks using sound level meter
- Detailed noise at work assessment using doseBadges

### Overview

The Economy Combination Kit is ideal for smaller industries with a lower number of mobile workers. The CR308 is a Calibrated Class 2 Sound Level Meter and can be used for spot checks. The doseBadge Pro Noise Dosimeters are used for direct measurement of a worker's noise exposure.

With this kit we recommend using the doseBadges for your full occupational noise survey as they provide all the measurements that are needed. The hand-held meter is a calibrated Class 2 sound level meter, but is not integrating (required by some regulations) and so does not provide measurements such as LAeq or Lavg. This meter is perfect for spot checks in addition to a survey carried out with the dosimeters.

For more comprehensive checks using a hand-held meter, please have a look at the Integrating Combination Kit.

### Kit Contents

The Economy Combination Kit comes with the following:

- doseBadge Pro noise dosimeter(s)
- doseBadge Charger and USB Dock
- CR308 Sound Level Meter
- CR514 Sound Level Calibrator
- NoiseTools Software
- Strong, weatherproof carry case
- Calibration certificates for meter, dosimeters and calibrator

## Economy Occupational Noise Combination Kit

### Specifications

#### doseBadge Pro Noise Dosimeter Specifications

|               |  |
|---------------|--|
| Standards     | IEC 61252 Personal Sound Exposure Meters<br>ANSI S1.25 Personal Noise Dosimeters |
| Range         | RMS: 60 to 140 dB(A), Peak: 80 to 143 dB   |
| Octave Bands  | Real-time, 63Hz to 8kHz  |
| Parameters    | Date/time, Leq, Lavg, TWA, LEP,d, Lex,8, %Dose, Peak                             |
| Communication | Bluetooth to mobile app, USB to computer   |
| Programmable  | Exchange rate, criterion level & time, Threshold, Time Weighting                 |
| Logging       | 1 second or 1 minute time history (user selectable)                              |
| Dimensions    | 66 x 43 x 53mm, 2.54" x 1.69" x 2.01"  |

For more detailed specifications please visit the doseBadge Pro Noise Dosimeter page.

#### CR308 Sound Level Meter Specifications

|                 |                                       |
|-----------------|---------------------------------------|
| Standards       | IEC 61672 Class 2<br>ANSI S1.4 Type 2 |
| Range           | 30 to 130 dB(A), 40 to 130 dB(C)      |
| Freq. Weighting | A and C                               |
| Time Weighting  | Fast and Slow                         |
| Functions       | Sound level, max, min, Peak           |
| Flags           | Alarm limit, overload, under-range    |
| Resolution      | 0.1 dB                                |
| Power           | 2 x AA / LR6 1.5V batteries           |

For more detailed specifications please visit the CR308 Sound Level Meter page.

---

#### Head Office

NoiseMeters Inc  
3233 Coolidge Hwy  
Berkley  
MI 48072  
USA

Telephone **888 206 4377**  
Fax **888 584 2230**

Email: **info@noisemeters.ca**  
Support: **support@noisemeters.ca**

#### Web Sites

Main site:  
<https://www.noisemeters.ca>

Product shortcut:  
<https://www.noisemeters.ca/p/cmb308/1/>

Tech Support:  
<https://support.noisemeters.com>